



## External accessories

### Flange handle operators

#### T4 & T5

#### Flange handle — Cable linkage

Breaker	NEMA Type	Mechanism only	List price	Cable only	Cable length	List price	Handle only	List price
T4	1, 3R, 12	KT4FPM	<b>\$ 148</b>	K5C036	36" (91 <sub>cm</sub> )	<b>\$ 114</b>	K5FCH	<b>\$ 213</b>
T4	4, 4X	KT4FPM		K5C048	48" (122 <sub>cm</sub> )	<b>146</b>	K5FCH4	<b>243</b>
T5	1, 3R, 12	KT5FPM	<b>193</b>	K5C060	60" (152 <sub>cm</sub> )	<b>160</b>	K5FCH	<b>213</b>
T5	4, 4X	KT5FPM		K5C060	72" (183 <sub>cm</sub> )	<b>175</b>	K5FCH4	<b>243</b>
-	-	-	-	K5C084	84" (213 <sub>cm</sub> )	<b>204</b>	-	-
-	-	-	-	K5C096	96" (244 <sub>cm</sub> )	<b>221</b>	-	-
-	-	-	-	K5C108	108" (274 <sub>cm</sub> )	<b>238</b>	-	-
-	-	-	-	K5C120	120" (305 <sub>cm</sub> )	<b>256</b>	-	-

**Notes:** For complete assembly; mechanism, cable and handle are required.  
 All cables mount onto the right side of the breaker.  
 Handle can be mounted on the right or left side.

#### Door hardware kits – T4 & T5 Cable operated

Item	Catalog number	List price
Door hardware kit, right hand, 2 point latch for enclosures less than 40 inches high	KDH2R	<b>\$ 200</b>
Door hardware kit, right hand, 3 point latch for enclosures 40 inches high or greater	KDH3R	<b>225</b>

#### Enclosure depths

##### Minimum

Breaker	Depth (inches)
T4 & T5	<b>8</b>

##### Maximum

Maximum depth is determined by cable length.