

## Other configurations

### NFC fuse pattern


### 63A – 125A, 14x51 & 22x58



OS32F1214



OS63F12



OS125F03

#### NFC fuse pattern switches (cylinder) (10x38) (14x51)

Handle and shaft included

Catalog number	Number of poles	Rated op. current/ Rated op. power		Fuse type and size	Fuse standard
		415V	690V		
OS25F1210 OS25F2210N1 OS25F2210F	3 3 + non-fused neutral 4	25 A 12 kW	25A 22 kW	10 x 38 25 A	IEC 269-2-1
OS32F1214 OS32F2214N1 OS32F2214F	3 3 + non-fused neutral 4	32 A 15 kW	32A 25 kW	14 x 51 32 A	IEC 269-2-1

#### NFC fuse pattern (cylinder fuse links), (14x51 & 22x58)

Handle and shaft included

Catalog number	Number of poles	Rated operational voltage AC23/[V]	I <sub>in</sub> (open) [A]	Rated operational power in category AC23A, IEC947 [A/kW]					Weight with pack- age [kg]
				230V	400V	415V	550V	690V	
OS50F12	3	690	50	50/15	50/25	50/25	50/33	50/45	1.3
OS50F22F	4	690	50	50/15	50/25	50/25	50/33	50/45	1.6
OS63F12	3	690	63	63/18.5	63/30	63/30	63/37	63/60	1.3
OS63F22F	4	690	63	63/18.5	63/30	63/30	63/37	63/60	1.6
OS100F03	3	690	125	100/30	100/45	100/55	100/60	100/90	2.2
OS100F04F	4								2.8
OS100F04N1	3 + non-fuse N								2.8
OS125F03	3	690	125	125/37	125/60	125/60	125/80	125/110	1.3
OS125F04F	4								1.6
OS125F04N1	3 + non-fuse N								1.6



NFC fuses are used in France and in French speaking Africa

① Please consult factory for additional information.