

General information Catalog number explanation

A110 SR F 1 - 84 C 6 D A

3

Starter size

Starter type

S - Non-reversing
SR - Reversing
SS - Single phase, non-reversing
N - NEMA

Combination type

N - Non-fusible disconnect
F - Fusible disconnect
B - Thermal magnetic or electronic trip type circuit breaker
M - Motor Circuit Protection (MCP)

Enclosure

1 - UL Type 1	7 - UL Type 7 & 9
2 - UL Type 12	Class I, Group D, Div 1 & 2
3 - UL Type 3R	Class II, Groups E, F & G, Div 1 & 2
4 - UL Type 4	Class III
X - UL Type 4X stainless steel	74 - Hazardous Type 4
P - Plastic	

Coil voltage/CCT

Overload range

See Overload Relay Selection chart, see page 3.6.

Accessories

See Factory modifications, page 3.3.

Fuse clip

6A - 30A, 600V, Class J
6B - 60A, 600V, Class J
6C - 100A, 600V, Class J
6D - 200A, 600V, Class J
6E - 400A, 600V, Class J
6F - 600A, 600V, Class J
6G - 800A, 600V, Class L
6H - 1200A, 600V, Class L

Circuit breaker amp rating (600V)

6D -15	6M-70	6W - 225	6E - 700
6E -20	6N - 80	6X - 250	6F - 800
6F -25	6P - 90	6Y - 300	6G - 900
6G -30	6R - 100	6Z - 350	6H - 1000
6H-35	6S - 125	6A - 400	6J - 1200
6J -40	6T - 150	6B - 450	
6K -50	6U - 175	6C - 500	
6L-60	6V - 200	6D - 600	

Circuit breaker amp rating (200V - 480V)

4D -15	4M-70	4W - 225	4E - 700
4E -20	4N - 80	4X - 250	4F - 800
4F -25	4P - 90	4Y - 300	4G - 900
4G -30	4R - 100	4Z - 350	4H - 1000
4H-35	4S - 125	4A - 400	4J - 1200
4J -40	4T - 150	4B - 450	
4K -50	4U - 175	4C - 500	
4L-60	4V - 200	4D - 600	

MCP amp rating (600V)

6A - 3	6D - 25	6G -	1506K	-600
6N - 1200				
6B - 5	6E - 50	6H -	2506L	-800
6C - 10	6F - 100	6J -	4006M	-1000

MCP amp rating (200V - 480V)

4A - 3	4D - 25	4G -150	4K - 600	
4N - 1200				
4B - 5	4E - 50	4H -	2504L	-800
4C - 10	4F - 100	4J -	4004M	-1200