

Control relays K622 - K640 AC & DC operated



K640-1



KC631-1

Control relays with screw connections

	Contact configuration		Catalog number	List price
	N.O.	N.C.		
AC Operated	4 3 2	0 1 2	K640-★ K631-★ K622-★	\$ 48
DC Operated	4 3 2	0 1 2	KC640-★ KC631-★ KC622-★	54

Control relays with flat pin connections

	Contact configuration		Catalog number	List price
	N.O.	N.C.		
AC Operated	4 3 2	0 1 2	K640FP-★ K631FP-★ K622FP-★	\$ 48
DC Operated	4 3 2	0 1 2	KC640FP-★ KC631FP-★ KC622FP-★	54

Control relays with soldering pin connections

	Contact configuration		Catalog number	List price
	N.O.	N.C.		
AC Operated	4 3 2	0 1 2	K640SP-★ K631SP-★ K622SP-★	\$ 48
DC Operated	4 3 2	0 1 2	KC640SP-★ KC631SP-★ KC622SP-★	54

Coil voltage selection

★ Coil voltage suffix. Refer to Coil Voltage Selection Chart and substitute the desired coil voltage suffix for the ★.

Coil voltage selection chart

	Volts								
	12	24	42	48	110/125	110/120	220	220/240	380/415
AC 40-450 Hz		F	L	G		1		2	M
DC	U	Y	V	W	P		R		