

Circuit breaker type A9 - AF750 Non-reversing, three phase

Combination
starters

3

UL Type 4 (Watertight)		UL Type 4X (Stainless steel)		UL Type 1, 3R, 4, 4X & 12 (Plastic)		UL Listed 7 & 9 non-reversing (Explosion proof)	
Catalog number	List price	Catalog number	List price	Catalog number	List price	Catalog number	List price
UL rated							
11M4-2Δ‡	\$ 1,260	11MX-2Δ‡	\$ 1,835	11MP-2Δ‡	\$ 1,050	11M7-2Δ‡	\$ 2,660
21M4-2Δ‡	1,290	21MX-2Δ‡	1,865	21MP-2Δ‡	1,080	21M7-2Δ‡	2,850
31M4-2Δ‡	1,320	31MX-2Δ‡	1,895	31MP-2Δ‡	1,110	31M7-2Δ‡	3,030
41M4-2Δ‡	1,410	41MX-2Δ‡	2,000	41MP-2Δ‡	1,193	41M7-2Δ‡	3,105
51M4-2Δ‡	1,500	51MX-2Δ‡	2,330	51MP-2Δ‡	1,275	51M7-2Δ‡	3,480
61M4-2Δ‡	1,635	61MX-2Δ‡	2,720	61MP-2Δ‡	1,380	61M7-2Δ‡	3,860
71M4-2Δ‡	2,115	71MX-2Δ‡	3,275	71MP-2Δ‡	1,875	71M7-2Δ‡	4,150
81M4-2Δ‡	2,438	81MX-2Δ‡	3,635	81MP-2Δ‡	2,100	81M7-2Δ‡	5,540
91M4-2Δ‡	3,225	91MX-2Δ‡	4,055	91MP-2Δ‡	2,520	91M7-2Δ‡	6,850
A1M4-2Δ‡	4,200	A1MX-2Δ‡	6,050	A1MP-2Δ‡	3,700	A1M7-2Δ‡	11,370
B1M4-2Δ‡	5,588	B1MX-2Δ‡	7,650	B1MP-2Δ‡	5,400	B1M7-2Δ‡	13,595
C1M4-2Δ‡	6,300	C1MX-2Δ‡	9,150	C1MP-2Δ‡	6,150	C1M7-2Δ‡	14,475
D1M4-2Δ‡	9,713	D1MX-2Δ‡	12,510	D1MP-2Δ‡	9,500	D1M7-2Δ‡	17,775
E1M4-2Δ‡	10,950	E1MX-2Δ‡	17,250	E1MP-2Δ‡	10,650	—	—
F1M4-2Δ‡	12,000	F1MX-2Δ‡	22,800	F1MP-2Δ‡	11,500	—	—
G1M4-2Δ‡	13,800	G1MX-2Δ‡	26,850	—	—	—	—
H1M4-70Δ‡	22,500	H1MX-70Δ‡	28,995	—	—	—	—
T1M4-70Δ‡	26,850	T1MX-70Δ‡	36,000	—	—	—	—
U1M4-70Δ‡	30,000	U1MX-70Δ‡	37,650	—	—	—	—

Δ Overload relay suffix code. Select from the overload relay selection chart on pages 3.6 - 3.7. Overload relays are required for all combination starters. If overload relay is provided by customer, substitute an "X" in place of the Δ and then subtract list price of overload relay from combination starter's list price.

‡ MCP or breaker rating. See codes on page 3.51.

Motor circuit protector data

Motor full load amperes	MCP continuous rating	Suffix code ‡	Catalog number	Starter size	1.5X	2X	4X	5X	6X	7X	8X	9X	10X	11X	12X
.92 - 2.76	3	1	S3L003MW	0	—	—	12	15	18	21	24	27	30	33	36
1.53 - 4.61	5	2	S3L005MW	0	—	—	20	25	30	35	40	45	50	55	60
3.07 - 9.23	10	3	S3L010MW	0	—	—	40	50	60	70	80	90	100	110	120
7.69 - 23.08	25	4	S3L025MW	1	—	—	100	125	150	175	200	225	250	275	300
15.38 - 46.15	50	5	S3L050MW	2	—	—	200	250	300	350	400	450	500	550	600
30.77 - 92.31	100	6	S3L100MW	3	—	—	400	500	600	700	800	900	1000	1100	1200
46.15 - 138.46	150	7	S3L150MW	4	—	—	600	750	900	1050	1200	1350	1500	1650	1800
28.85 - 230.77	250	8	S4L250MW	4	375	500	1000	—	1500	—	2000	—	2500	—	3000
46.15 - 369.23	400	9	S5L400MW	5	600	800	1600	—	2400	—	3200	—	4000	—	4800
69.23 - 553.85	600	C	S6L600MW	6	900	1200	2400	—	3600	—	4800	—	6000	—	7200
92.31 - 738.46	800	E	S6L800MW	7	1200	1600	3200	—	4800	—	6400	—	8000	—	9600
115.38 - 923.07	1000	G	S7H1000MW	7	1500	2000	4000	—	6000	—	8000	—	10,000	—	12,000
138.46 - 1107.69	1200	H	S7H1200MW	7	1800	2400	4800	—	7200	—	9600	—	12,000	—	14,400